




DATA SHEET - CONICAL CONCRETE BUCKET WITH BOTTOM DISCHARGE AND FORKLIFT POCKETS





Code	Capacity (kg)	Capacity (L)	Weight (kg)	Dimensions (mm)					
				Α	В	С	D	E	F
C-15ST	390	150	55	620	920	750	1050	174	74
C-20ST	520	200	60	700	920	750	1050	174	74
C-25ST	650	250	65	780	920	750	1050	174	74
C-30ST	780	300	70	860	920	750	1050	174	74
C-35ST	910	350	75	940	920	750	1050	174	74
C-40ST	1040	400	85	890	1050	880	1200	174	74
C-50ST	1300	500	95	1010	1050	880	1200	174	74
C-60ST	1560	600	125	1130	1050	880	1200	174	74
C-80ST	2080	800	160	1180	1250	750	1450	174	74
C-99ST	2600	1000	180	1360	1250	750	1450	174	74













Conical concrete bucket with bottom discharge and forklift pockets

Conical concrete bucket with central discharge, forkliftable base and lever opening

The C-ST model, characterized by a central discharge, ensures precise and controlled dosing through its lever-operated opening, guaranteeing high-quality and safe concrete pouring throughout the process. A distinctive feature of this model is its sturdy fork base (internal section 174×74h mm), which allows the bucket to be lifted and moved both with a forklift or telescopic handler and with a construction crane through the lifting arc. Available in various sizes and capacities, the C-ST model adapts to the diverse needs of the construction site, ensuring flexibility and versatility. Its intuitive design facilitates usage, ensuring high operational efficiency and optimal results on site. Each bucket is built and tested according to stringent standards of UNI EN ISO 12100, UNI EN 13854, ISO 8686, UNI EN 10027, and UNI EN 10204, guaranteeing the highest quality and safety of our products. Each item comes with a metal ID plate, a certificate of conformity, and an operation and maintenance manual. Our Model C-ST conical bucket is covered by a one-year warranty in compliance with the European Directive. Choose our solution for efficient and reliable work experiences in the concrete sector.

Application sectors

Construction



