

**DATA SHEET - LAYDOWN CONICAL CONCRETE KIBBLE WITH LEVERED OPENING**



Code	Capacity (kg)	Capacity (L)	Weight (kg)	Dimensions (mm)			
				A	B	C	D
BCF-30L	780	300	265	1965	1270	627	1495
BCF-50L	1300	500	275	2098	1270	643	1512
BCF-75L	1950	750	320	2385	1530	763	1782
BCF-99L	2600	1000	355	2570	1530	786	1806
BCF-150L	3900	1500	690	2781	1885	975	2033
BCF-200L	5200	2000	720	3031	1885	975	2033

## DATA SHEET - LAYDOWN CONICAL CONCRETE KIBBLE WITH LEVERED OPENING

### Concrete buckets



## Laydown conical concrete kibble with levered opening

### Laydown conical concrete bucket with central discharge and lever opening

We are excited to present the BCF-L model, a laydown conical bucket designed to offer reliable and versatile performance on your construction site. Equipped with a bivalve opening operated by a lever and a central discharge, this bucket boasts a robust and durable design. The presence of a spring allows for automatic closure of the discharge, while a rope enables the bucket to be opened even at height. A unique feature of this bucket model is the horizontal ground loading method, which makes the bucket, even if of large capacity, very low at the edge, facilitating filling with the concrete mixer without any impediments. Available in a variety of sizes and capacities, the BCF-L model can be customized with the addition of a rubber hose or a handwheel opening. All our buckets are built and tested in accordance with the strict standards UNI EN ISO 12100, UNI EN 13854, ISO 8686, UNI EN 10027, and UNI EN 10204. Each product comes with a metal ID plate, a certificate of conformity, and a user and maintenance manual to ensure proper use over time. Additionally, all our products are covered by a one-year warranty, in compliance with the European Directive.

### Application sectors

 Construction